

Mobile Demineralizer Trailers

Mobile Demineralizer Trailers provide a reliable supply of high quality demineralized water for nearly any application. With our mobile demineralizer trailer fleet, and strict quality control standards, we are able to respond to nearly any mobile DI water requirement. Each trailer also includes Water Linx, our remote monitoring platform for detailed performance data analysis.

Typical Uses

- ✓ Capacity Expansions
- ✓ Zero Discharge Mobiles
- ✓ Interim Use
- ✓ Process Water Changes
- ✓ Scheduled Shutdowns
- ✓ Emergency Water Needs



Specifications

Resin Capacity	Up To 630 CFT 10 Million Grain
Flow Rate min/max	50 gpm / 400 gpm
Dimensions L x W x H	53' x 8.5' x 13.5'
Electrical Requirements	(2) 115 V, single phase, 60 hz, 20 amps
Instrumentation	Conductivity on feed and effluent, flow indicator and flow totalizer, pressure gauges, quality sample ports, and Water Linx remote monitoring service
Typical Water Quality	Conductivity <0.06 μ S, Silica < 10 ppb

*Based on a 1 μ S/cm end point



Water Linx Remote Monitoring Service Included



24 / 7 Dispatch



No Capital Investment



Flexible Configuration

